



Ditec Automatic pedestrian doors

EN

DISTI

Ditec automatic doors.

A sign of distinction.

Comfort, safety, prestige, hygiene, appeal, access control and, in the case of air-conditioned areas, optimised energy consumption: these are just some of the advantages of having an automatic door outside as well as inside.



ACTIVE CLASS

Today's life has made it more and more frequent and common to find doors that open when we get near them. Thanks to cutting-edge technology, superior quality of processes and materials, our automatic sliding doors, opening and closing smoothly and trouble-free, not only give the building something more in terms of look, novelty and appeal but they also make the life of the people using them more and more comfortable. This is why having an automatic door is not only a question of image and adaptation to advanced technical solutions, it also shows care for the people that come and go, making their life easier.

Automatic doors also provide an ideal means to solve problems arising from architectural barriers.

A comprehensive and certified range

Ditec is the widest automation range available for straight-line sliding pedestrian doors, capable of satisfying any particular requirement or performance: from the high-opening speed automatic systems for high-traffic entrances, to the smooth and controlled motion systems for house installations. These automatic systems are easy to install and come in a variety of aesthetic solutions that can match any type of furniture. Ditec also provides solutions with specially designed antipanic devices, designed to increase safety levels and to facilitate access to escape routes in emergencies. The following tables allow customers to select the most suitable automation for individual requirements and to check their comprehensive and advanced technical features.



Ditec Valor



High-tech, exceptionally well designed
top of the range
For continuous duty

Ditec Valor is the straight sliding automatic door designed with great attention to details to meet the most demanding requirements for commercial applications. Ditec Valor has gained a leading position in the marketplace as it features very advanced technologies, last generation electromechanical components, an innovative control panel, very quiet, smooth operation ensured by the vibration proof sliding guide.

Multiple operational situations

Ditec Valor sliding door is specially suitable for heavy duty, continuous use applications, such as in public areas, large shopping centres and airports, where the high traffic requires a more demanding operation compared to other locations.

Self-adjustment of the door opening

In air conditioned rooms, Ditec Valor ensures better power consumption thanks to the automatic closing time and access opening auto set-up according to the number of people crossing the doors. In high pedestrian traffic areas, Ditec Valor increases the automatic opening time, whilst the transit opening can be partly opened if the number of people going through the door is not very high.

Product range

	Capacity	Duty
Valor L	up to 180 kg	very heavy
Valor P	up to 220 kg	continuous
Valor N	up to 300 kg	continuous
Valor T	up to 260 kg	continuous and telescopic
Valor HS	up to 500 kg	continuous



Comprehensive, solid, versatile and quiet

A wide array of functions

Designed to offer a versatile and comprehensive product, it features a range of exclusive, major features which make it suitable for the most diverse operating conditions:

- **Advanced electronics**, thanks to the electronic panel with all on-board basic settings and to the built-in photocell amplifier
- **Automatic opening time auto set-up**. With high pedestrian traffic, the automation automatically increases the opening time
- **Transit opening auto set-up**. With high pedestrian traffic, the automation automatically switches from partly to fully opened
- **Built-in safety sensors**. In all models, all sensors may be fitted under the guard, with clear aesthetic benefits
- **MP1 electronic PCB**, added to extend the control functions available
- **Quiet operation**. Thanks to the vibration proof seal located under the sliding guide, on all models the Ditec Valor range ensures a smoother operation
- **Self supporting facility** on all models (excluding Ditec Valor L and P)
- **Equipped with a wide range of accessories**. Batteries with emergency or UPS facility can be selected, as well as a release system built in the automation
- **Operating unit**. Monobloc control/drive system with direct current gear motor with encoder, control and monitoring panel, with new generation microprocessor based logic, which allows to remotely set up and control the automation from the display or a computer
- **On-board or remote control**. As well as being easily monitored by means of a remote monitoring system **DMCS** (Door Monitoring & Controlling System), the Ditec Valor control panel is connected to a **MD1 display** built in the head or wall mounted, to monitor and set up the following functions: diagnostics, maintenance alarm, opening setting, control panel function display
- **Dedicated frames**. Every Ditec Valor automation has been designed to match the **Ditec PAM** profile series, but can also be used with commercially available profiles.

MD1 DISPLAY MODULE

Using the controls from the electronic panel

Password management

Electronic panel firmware version display

MP1, MD1 firmware version display

Total/partial operations display

Maintenance alarm setting

Safety, alarm and fault display

Automation status display

Automatic closing time and access opening auto set-up

Partial to total opening automatic switching

PLUS MP1 MODULE

Accessory dedicated electrical connections

Manual closing control

Contact for opening key

Contact for closing key

Contact for people access visual/audio indicators

Dedicated connection for safety sensors equipped with safety test monitoring facility

General Purpose outputs

Output for spot light; Air blade power supply

Battery status monitoring facility with advanced test, to allow emergency opening

Emergency-Exit Systems: when every second counts

Ditec Valor provides reliable opening and closing also along escape routes: two types of solution are available: **anti-panic breakout systems** and **redundant systems**.

The anti-panic breakout door has all the same features as a standard automatic door. However, in case of an emergency, the users can manually open the wings of the door and, where applicable, also the semi-fixed side wings in the same direction as flight: with this system the wings open like a swing door guaranteeing generous passing space, almost equal to the width of the entire door.

The second type of system uses the principle of redundancy of the electrical and electromechanical components performing periodic checks of the operation of the complete system.

The operating unit and all accessories have been designed to guarantee that the door opens in the event of:

- emergency
- loss of power
- partial or complete system breakdown or malfunction.




TÜV Certified Anti-Panic Features for Escape Routes

Ditec Valor

Technical specifications

	Valor L	Valor P	Valor N	Valor T	Valor HS
Description	automation for sliding doors	automation for sliding doors	automation for sliding doors	automation for telescopic sliding doors	automation for heavy sliding doors
Special uses	emergency breakout and redundant exit	emergency breakout and redundant exit	emergency breakout and redundant exit	redundant emergency system	
Stroke control	encoder	encoder	encoder	encoder	encoder
Capacity	100 kg (1 wing) 180 kg (2 wings)	120 kg (1 wing) 220 kg (2 wings) 100 kg (1 breakaway wing) 180 kg (2 breakaway wings)	120 kg (1 wing) 240 kg (2 wings)	200 kg (2 wings) 260 kg (4 wings)	class 4: 200 kg (1 wing) 340 kg (2 wings) class 5: 170 kg (1 wing) 300 kg (2 wings)
Capacity with reinforced wheels			150 kg (1 wing) 300 kg (2 wings)		
Capacity with 2 wheels for runner					class 5: 300 kg (1 wing) 360 kg (2 wings) class 6: 220 kg (1 wing) 300 kg (2 wings)
Capacity with 2 wheels for runner and 3rd runner					class 4: 450 kg (1 wing) 500 kg (2 wings) class 5: 350 kg (1 wing) 400 kg (2 wings)
Duty class	5 - heavy duty	6 - continuous	6 - continuous	6 - continuous	4 - intensive 5 - heavy duty 6 - continuous
Intermittent operation	S3 = 100%	S3 = 100%	S3 = 100%	S3 = 100%	class 4: S2 = 20 min S3 = 30% class 5: S2 = 60 min S3 = 60% class 6: S3 = 100%
Power supply	230 V AC / 50-60 Hz	230 V AC / 50-60 Hz	230 V AC / 50-60 Hz	230 V AC / 50-60 Hz	230 V AC / 50-60 Hz
Power input	1 A	1 A (1.6 A with weight > 200 kg)	1 A (1.6 A with weight > 200 kg)	1 A	1 A
Maximum opening and closing speed	0.8 m/s (1 wing) 1.6 m/s (2 wings)	1 wing: 0.8 m/s 2 wings: 1.6 m/s (1.2 m/s with weight > 180 kg)	1 wing: 0.8 m/s 2 wings: 1.6 m/s (1.2 m/s with weight > 200 kg)	0.8 m/s (2 wings) 1.6 m/s (4 wings)	0.5 m/s (1 wing) 1.0 m/s (2 wings)
Release system for manual opening	built-in handle	built-in handle	built-in handle	handle	handle
Operating temperature	-20°C / +55°C (-10°C / +50°C batteries)	-20°C / +55°C (-10°C / +50°C batteries)	-20°C / +55°C (-10°C / +50°C batteries)	-20°C / +55°C (-10°C / +50°C batteries)	-20°C / +55°C (-10°C / +50°C batteries)
Protection rating	IP 20	IP 20	IP 20	IP 20	IP 20
Product dimensions (mm)	175 x 145 x L	175 x 145 x L	175 x 145 x L	255 x 145 x L	150 x 300 x L
Approvals	TÜV	TÜV	TÜV	TÜV	
Control panel	EL20 (built-in)	EL20 (built-in)	EL20 (built-in)	EL20 (built-in)	EL32 (built-in)

Main system functions

	Valor L - Valor P - Valor N - Valor T	Valor HS
Control panel	EL20	EL32
Mains power supply	230 V AC / 50-60 Hz	230 V AC / 50-60 Hz
Batteries	■ (optional)	■ (optional)
 Energy saving	reduced consumption when in use	reduced consumption when in use
Number of motors	1	1
Motor power supply	24 V DC / 10 A	24 V DC / 15 A
Accessories power supply	24 V DC / 0.5 A	24 V DC / 0.5 A
Electrically operated lock	24 V DC / 1 A	24 V DC / 1 A
Courtesy light	■ (with MP1)	■ (with MP1)
Encoder speed and deceleration control	■	■
Force adjustment control	electronics	electronics
ODS - Obstruction detection system	■	■
Speed adjustment	■	■
Braking / Deceleration	■	■
Open control	■	■
Partly open control	■	■
Close control	■ (optional with MP1)	■ (optional with MP1)
Automatic timed close control	■	■
Stop safety device	■	■
Reverse operation safety device	■	■
Safety test facility	■	■
Built-in photocell amplifier	■	■



Relevant Directives and Standards

MD
Machine Directive

EMCD
Compatibility Directive
Electromagnetic

LVD
Low Voltage Directive

EN 16005
User Safety Standard

**More comfort in your environment,
more freedom in your life with the
automation for Ditec swing doors.**
They make the environment unique
and comfortable and greatly assist
older people or those less fortunate in
carrying out everyday activities such
as opening and closing doors.

FR

E



Systems for frames

Frames for sliding automatic entrances

Ditec frames are the best functional and technical choice, supported by decades of experience in the field, to the benefit of our customers.

The wide range of solutions offered allows Ditec frames to be fitted in any architectural context, embedding the entrance with elegance and harmony in compliance with the strictest Standards and European Directives.

The basic concepts that characterise our systems for frames are:

- maximum simplicity of assembly
- maximum simplicity of installation
- certified and guaranteed safety.

Full range of frames for all types of entrances available:

- sliding doors with 1 or 2 wings, up to 4 telescopic wings
- doors prepared with reliable devices which allow the mechanical breakout of the wings simply by applying pressure, guaranteeing safe evacuation in case of fire
- elegant doors created completely in glass or framed in sturdy structures to satisfy any technical and aesthetic requirements.

The solutions offered

There are 3 variants available:

1. **Components for frames:** profiles (mill finish or anodised in natural colour), accessories and seals, complete with

manuals and technical specifications for the complete production of entrances. Working, assembly and installation by the customer.

2. **Frames in kits:** custom-made, in the colour requested complete with all components, with instructions for subsequent assembly and installation by the customer (glass excluded)
3. **Pre-assembled frames:** custom finished, in the colour requested, and assembled, complete with all components, with instructions for installation by the customer (glass included)



When building the system, only use Ditec accessories and safety devices.

Every Ditec automation features CE marking and is designed and built in compliance with the safety requirements of the Machinery Directive (2006/42/EC), of the Electromagnetic Compatibility Directive (2004/108/EC) and of the Low Voltage Directive (2006/95/EC) and of other Directives, laws, specific standards for special products and situations.

The Company reserves the right to make changes which may improve the products.

For this reason, the technical details given are not binding.

Pictures were taken with the consent of those concerned or in public locations.

Further information can be found in the Technical Manuals available at the website: **www.ditecentrematic.com**

ENTRE//MATIC



Entrematic Italy S.p.A.

Via Mons. Banfi, 3 • 21042 Caronno P.lla (VA) • Italy

Tel +39 02 963911 • Fax: +39 02 9650314

ditec@entrematic.com

www.ditecentrematic.com • www.entrematic.com

Cod. P200B - Rev. 1 - 07/2014
Automatic pedestrian doors
gdp milano 140265

Ditec branches are in: France, Germany, Portugal, Spain, Sweden, Turkey, USA and Canada.
For addresses and contacts visit our website www.ditecentrematic.com

